



BARRIER® M UV SYSTEMS

WALLACE & TIERNAN® UV DISINFECTION SYSTEMS

The Barrier® M range of UV systems is primarily designed for the treatment of water with flow rates ranging from 10 to 1150 m³/h (44 to 5000 US gpm). It is equipped with Wallace & Tiernan® medium-pressure lamps, type WTL and electrical ballasts. The wide emission spectrum of the lamps, ranging from 200 to 300 nm, attacks the nucleic acid (DNA), cell wall, proteins and enzymes of waterborne pathogens. Such attacks not only inactivate the microorganism by preventing the replication of its DNA, but also destroy its repair mechanisms. A wide range of DVGW certified systems is available. The Barrier® M system reaction chamber is characterised by optimal hydraulics and low pressure loss, ensuring a high efficiency of the UV system.

Applications

- Potable water
- Swimming pools, including chloramines reduction and disinfection
- Industrial process and wastewater, e.g. food & beverage, pharmaceutical, and fish hatcheries
- Small and medium size wastewater plants

Standard Features

- Optimised operation through variable power control
- Absolute calibrated UV sensor for optimal performance control
- Hydrodynamically optimised chamber design
- Simple, easy-to-use user interface
- Reaction chamber made of stainless steel AISI 316L, particular systems made of 318 LN for seawater available

Key Benefits

- Low operation costs and low head loss through low number of powerful medium-pressure lamps
- Extended lamp life and energy efficient operation through accurate lamp power control
- Low installation costs through space saving design and small footprint, easy installation and retrofit with in-line design
- Wide UV spectrum leads to effective treatment of photoreactivation
- Low life cycle costs with hydrodynamically optimised chamber design

Optional Features

- Manual or automatic cleaning system (automatic for Barrier M 80 system or larger)
- DVGW certification for Barrier M 275, 525, 900, 1250, 2600 and 3800 systems
- Chemical cleaning system

Model	Disinfection capacity ¹	T ₉₀ mm	Chloramine reduction capacity ²	Connection flange acc. DIN EN 1092-1ANSI	Power consumption ³	Electrical supply	WTL Lamps	Weight dry	Dimensions UV chamber (A x H x L) ⁴	Dimensions Control panel ⁷ H x W x D
M 35	33 m ³ /h 145 gpm	98%	19 m ³ /h 84 gpm	DN 80 3" 150-lb	880 W	1/N/PE AC 208-277 V, 50-60 Hz (IEC) 2/PE AC 208-277 V, 50-60 Hz, 1-phase 2-wire (USA)	1 x 1000	14 kg 31 lbs	300 x 214 x 600 mm 11-13/16" x 8-7/16" x 23-10/16"	700 x 500 x 300 mm 27-9/16" x 19-11/16" x 11-13/16"
M 80	70 m ³ /h 308 gpm	98%	39 m ³ /h 172 gpm	DN 125 5" 150-lb	880 W	1/N/PE AC 208-277 V, 50-60 Hz (IEC) 2/PE AC 208-277 V, 50-60 Hz, 1-phase 2-wire (USA)	1 x 1000	59 kg 130 lbs	350 x 306 x 1000 mm 11-13/16" x 8-7/16" x 39-3/8"	700 x 500 x 300 mm 27-9/16" x 19-11/16" x 11-13/16"
M 135	112 m ³ /h 493 gpm	98%	61 m ³ /h 269 gpm	DN 125 5" 150-lb	1669 W	1/N/PE AC 208-277 V, 50-60 Hz (IEC) 2/PE AC 208-277 V, 50-60 Hz, 1-phase 2-wire (USA)	1 x 2000	59 kg 130 lbs	350 x 306 x 1000 mm 13-4/5" x 12" x 39-2/5"	700 x 500 x 300 mm 27-9/16" x 19-11/16" x 11-13/16"
M 210	116 m ³ /h 511 gpm	90%	n.a.	DN 125 5" 150-lb	3326 W	3/PE AC 208-277 V, 50-60 Hz, 3-phase 3-wire (USA) or 3/PE AC 360/208-480/277 V, 50-60 Hz, 3-phase 4-wire (USA)	4 x 1000	60 kg 132 lbs	350 x 306 x 1000 mm 13-4/5" x 12" x 39-2/5"	1125 x 800 x 400 mm 44-5/16" x 39-2/5" x 15-3/4"
M 275 ⁵	223 m ³ /h 982 gpm	98%	119 m ³ /h 524 gpm	DN 200 8" 150-lb	1669 W	1/N/PE AC 208-277 V, 50-60 Hz (IEC) 2/PE AC 208-277 V, 50-60 Hz, 1-phase 2-wire (USA)	1 x 2000	63 kg 139 lbs	V400 x 406 x 900 mm 15-3/4" x 16" x 35-1/2"	700 x 500 x 300 mm 27-9/16" x 19-11/16" x 11-13/16"
M 290	106 m ³ /h 467 gpm	85%	n.a.	DN 125 5" 150-lb	4899 W	*3/N/PE AC 360/208-480/277 V, 50-60 Hz (IEC) 3/PE AC 208-277 V, 50-60 Hz, 3-phase 3-wire (USA) or 3/PE AC 360/208-480/277 V, 50-60 Hz, 3-phase 4-wire (USA)	3 x 2000	60 kg 132 lbs	350 x 306 x 1000 mm 13-4/5" x 12" x 39-2/5"	1125 x 800 x 400 mm 44-5/16" x 39-2/5" x 15-3/4"
M 350	130 m ³ /h 572 gpm	85%	n.a.	DN 125 5" 150-lb	6484 W		4 x 2000	60 kg 132 lbs	350 x 306 x 1000 mm 13-4/5" x 12" x 39-2/5"	1125 x 800 x 400 mm 44-5/16" x 39-2/5" x 15-3/4"
M 525 ⁵	337 m ³ /h 1484 gpm	98%	176 m ³ /h 775 gpm	DN 200 8" 150-lb	3248 W		2 x 2000	64 kg 141 lbs	400 x 406 x 900 mm 15-3/4" x 16" x 35-1/2"	1125 x 800 x 400 mm 44-5/16" x 39-2/5" x 15-3/4"
M 700	313 m ³ /h 1378 gpm	90%	295 m ³ /h 1299 gpm	DN 200 8" 150-lb	4899 W		3 x 2000	64 kg 141 lbs	400 x 406 x 900 mm 15-3/4" x 16" x 35-1/5"	1125 x 800 x 400 mm 44-5/16" x 39-2/5" x 15-3/4"
M 900 ⁵	298 m ³ /h 1312 gpm	85%	n.a.	DN 200 8" 150-lb	6484 W		4 x 2000	64 kg 141 lbs	400 x 406 x 900 mm 15-3/4" x 16" x 35-1/2"	1125 x 800 x 400 mm 44-5/16" x 39-2/5" x 15-3/4"
M 950	6		402 m ³ /h 1770 gpm	DN 250 10" 150-lb	4899 W		3 x 2000	72 kg 159 lbs	400 x 406 x 900 mm 15-3/4" x 16" x 35-1/5"	1125 x 800 x 400 mm 44-5/16" x 39-2/5" x 15-3/4"
M 1200	6		528 m ³ /h 2325 gpm	DN 250 10" 150-lb	6484 W		4 x 2000	72 kg 59 lbs	400 x 406 x 900 mm 15-3/4" x 16" x 35-1/2"	1125 x 800 x 400 mm 44-5/16" x 39-2/5" x 15-3/4"
M 1250 ⁵	320 m ³ /h 1409 gpm	80%	n.a.	DN 200 8" 150-lb	9654 W		6 x 2000	64 kg 141 lbs	400 x 406 x 900 mm 15-3/4" x 16" x 35-1/2"	1125 x 800 x 400 mm 44-5/16" x 39-2/5" x 15-3/4"
M 1400	493 m ³ /h 2171 gpm	90%	n.a.	DN 350 14" 150-lb	4893 W		2 x 3500	160 kg 353 lbs	600 x 590 x 1000 mm 23-5/8" x 23-1/4" x 39-3/8"	1125 x 800 x 400 mm 44-5/16" x 39-2/5" x 15-3/4"
M 1700	6		653 m ³ /h 2875 gpm	DN 350 14" 150-lb	6484 W		4 x 2000	160 kg 353 lbs	600 x 590 x 1000 mm 23-5/8" x 23-1/4" x 39-3/8"	1125 x 800 x 400 mm 44-5/16" x 39-2/5" x 15-3/4"
M 2000	709 m ³ /h 3122 gpm	90%	750 m ³ /h 3302 gpm	DN 350 14" 150-lb	7267 W		3 x 3500	160 kg 353 lbs	600 x 590 x 1000 mm 39-2/5" x 23-1/4" x 39-2/5"	1125 x 800 x 400 mm 44-5/16" x 39-2/5" x 15-3/4"
M 2600 ⁵	923 m ³ /h 4064 gpm	90%	974 m ³ /h 4288 gpm	DN 350 14" 150-lb	9642 W		4 x 3500	160 kg 353 lbs	600 x 590 x 1000 mm 39-2/5" x 23-1/4" x 39-2/5"	1125 x 800 x 400 mm 44-5/16" x 39-2/5" x 15-3/4"
M 3800 ⁵	912 m ³ /h 4015 gpm	85%	n.a.	DN 350 14" 150-lb	14390 W		6 x 3500	160 kg 353 lbs	600 x 590 x 1000 mm 23-5/8" x 23-1/4" x 39-3/8"	1125 x 800 x 400 mm 44-5/16" x 39-2/5" x 15-3/4"

- Capacity at a UV dose of 400 J/m², end of lamp life, at the specified UV transmittance, and based on the multiple point source summation method
- Capacity at a UV dose of 600 J/m², end of lamp life, and a UV transmittance (254 nm; 1 cm cell) of 95 %
- Total average power consumption over 9000 h based on constant flow rate, UV transmittance and UV dose as used for the selection of this system (unless specified different)
- A x H x L: Assembly dimension x height x length
- Also available in DVGW certified execution; please consult factory or individual datasheet for biosymmetrical certified capacities (DVGW - Internationally recognised authority on certification of UV disinfection systems. DVGW - German Technical and Scientific Association for Gas and Water)
- When sized for chloramines reduction, this unit will achieve 4 logs inactivation of most waterborne pathogens (bacteria, viruses, protozoa)
- Wall mounted



885 Mountain Highway, Bayswater, VIC, 3153, Australia

1300 661 809 (Ph) / +61 3 8720 6597 (Int) 1300 661 708 (Fax) / +61 3 8720 6502 (Int) www.evoqua.com.au

Barrier and Wallace & Tiernana are trademarks of Evoqua, its subsidiaries or affiliates in some countries.

All information presented herein is believed reliable and in accordance with accepted engineering practices. Evoqua makes no warranties as to the completeness of this information. Users are responsible for evaluating individual product suitability for specific applications. Evoqua assumes no liability whatsoever for any special, indirect or consequential damages arising from the sale, resale or misuse of its products.

© 2014 Evoqua Water Technologies Pty Ltd Subject to change without notice WT-090.370.000-AU-DS-A4-0514