

PENTEK RO-2550 REVERSE OSMOSIS DRINKING WATER SYSTEM

REDUCES LEAD AND CHLORINE TASTE & ODOR



The Pentair Pentek* RO-2550 Reverse Osmosis (RO) Drinking Water System reduces lead, chlorine taste & odor, dissolved minerals & salts, copper, hexavalent & trivalent chromium, barium, radium 226/228, selenium, and cysts such as Cryptosporidium and Giardia by mechanical means.

The carbon/sediment pre-filter reduces the particles and chlorine taste and odor to prolong life of RO membrane. The RO membrane separates water molecules from dissolved salts and minerals. Up to 96% of these total dissolved solids (TDS) are rejected and sent down the drain. The RO filtered water is sent to the storage tank until you need it. When you turn on the drinking water faucet, the filtered water from the storage tank is sent through a carbon polishing filter which provides final taste and odor filtration before the water reaches your glass. Cleaner, fresher water whenever you want it!

FEATURES/BENEFITS

Includes 50 gallon per day reverse osmosis element

Installed under the sink

Water on demand delivered from a 2.8 gallon storage tank

Automatic shut-off valve helps conserve water

Reduces salts, dissolved minerals, bad taste and odor

Designed for chlorinated and non-chlorinated water

Reduces particles as small as 1/1000 of a micron in size by mechanical means

NSF/ANSI Standard 58 certified to reduce cysts such as Cryptosporidium and Giardia by mechanical means

APPLICATIONS

Provides cleaner, fresher tasting water for drinking and cooking



System Tested and Certified by NSF International against NSF/ANSI Standard 58.

EPA EST. NO. 082989-CHN-001

ORDERING INFORMATION

SYSTEM		SPECIFICATIONS						
MODEL	PART NUMBER	MAXIMUM DIMENSIONS	WEIGHT	TANK CAPACITY	PRESSURE RANGE	TEMPERATURE RANGE	MEMBRANE CAPACITY	TDS REJECTION
RO-2550	161079	System: 12" W x 6" D x 16" H (304mm W x 152mm D x 406mm H) Tank: 13-1/2" W x 9" D x 9" H (343mm W x 203mm D x 229mm H)	17.3 lbs (7.85 kg)	2.8 gallons (10.6 litres)	40 - 100 psi (3.45 - 6.89 bar)	40 - 100° F (4.4 - 37.8° C)	50 gallons per day (GPD)	96.2%



WATER QUALITY SYSTEMS

WATER QUALITY SYSTEMS
5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209
P: 262.238.4400 | F: 262.238.4404
WATERPURIFICATION.PENTAIR.COM
CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com
© 2015 Pentair Residential Filtration, LLC. All rights reserved.
*For a detailed list of where Pentair trademarks are registered, please visit waterpurification.pentair.com.

Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners.

4003285 REV A MY15