



AXEON® Flow Meters are offered in 1, 2, 5, 10, and 20 gallons per minute configurations. All flow meters have an

easy-to-read scale which has been silk-screened onto an acrylic body.

AXEON® Flow Meters offer durability, accuracy, and high quality.

Features:

- 1, 2, 5, 10, & 20 GPM Sizes Available
- Solid One Piece Injection Molded Acrylic Body
- Stainless Steel Float and Internals
- Models Available With 316 SS Integrated Needle Valve
- Permanent Screen Printed Scales
- Calibrations in GPM & LPM
- Individually Packaged
- 100% Tested for Accuracy

Technical Specifications:

Body: Acrylic

O-Rings: Silastic®

■ Connections: Polypropylene


Guide: 316 Stainless Steel

■ Float: 316 Stainless Steel

■ Maximum Pressure: 150 psi

■ Temperature Rating: 120°F

Accuracy: ±5% Accuracy





AXEON® Standard Flow Meters:										
Part Number:	GPM Range:	Integrated 316 SS Valve:	Inner Connection:	Outer Connection:	A	В	С	D	E	F
203849	0.1-1 GPM	No	1/4" FNPT	1/2" MNPT	6.93"	6.62"	5.00"	3.00"	1.250"	1.375"
200897	0.2-2 GPM	No	1/4" FNPT	1/2" MNPT	6.93"	6.62"	5.00"	3.00"	1.250"	1.375"
205103	0.2-2 GPM	Yes	1/4" FNPT	1/2" MNPT	6.93"	6.62"	5.00"	3.00"	1.250"	1.375"
200898	1-5 GPM	No	1/4" FNPT	1/2" MNPT	6.93"	6.62"	5.00"	3.00"	1.250"	1.375"
205104	1-5 GPM	Yes	1/4" FNPT	1/2" MNPT	6.93"	6.62"	5.00"	3.00"	1.250"	1.375"
200899	1-10 GPM	No	1/2" FNPT	1" MNPT	9.30"	9.00"	6.50"	4.00"	1.760"	1.760"
205105	1-10 GPM	Yes	1/2" FNPT	1" MNPT	9.30"	9.00"	6.50"	4.00"	1.760"	1.760"
200900	2-20 GPM	No	1/2" FNPT	1" MNPT	9.30"	9.00"	6.50"	4.00"	1.760"	1.760"
205106	2-20 GPM	Yes	1/2" FNPT	1" MNPT	9.30"	9.00"	6.50"	4.00"	1.760"	1.760"



Engineered Water Treatment Solutions

WATER TECHNOLOGIES

P: 800.320.4074 • 760.723.5417 • W: www.axeonwater.com

F: 760.728.5062 • E: sales@axeonwater.com • 541 Industrial Way, Suite 1, Fallbrook, CA 92028